## **Resolver Part Numbering System**

**PS-52 XX-XXX-X** X PLuS® Part Number HOUSING Resolver A - Can housing w/flange or foot endbells C - Stainless steel square housing **E** - 74 mm bolt spacing, flange mount **SHAFT SIZE S** - Servo mount (.12 = size 11; .38 - size 25) 12 - 1/8 DIA. 15 - 15 mm DIA. 20 - 20 mm DIA. 38 - 3/8" DIA., 2.06" Bolt Flange **TYPE OF CABLE CONNECTION** 62 - 5/8" DIA., 2.25" Bolt Flange D - Military bayonet style connector 75 - 3/4" DIA. T - Terminal strip with NO conduit entrance V - No connector, just stripped & tinned wires S - Sealed connector — screw type Note: "T" only available for PS-5262 stainless steel NEMA 4X 5/8" shaft resolver. Part# PS-5903-01-001 **RATIO** conduit entrance sold separately. 11 - Standard 1:1 (Note: 3rd digit not used on Standard 1:1.) 021 - Geared 2:1 - Ext. shaft to internal resolver shaft 361 - Geared 36:1 - Ext. shaft to internal resolver shaft Various ratios available — contact Factory. **LOCATION OF CABLE CONNECTION** W - With stripped & tinned leads **G** - Right (120° from top on "A" housings) **R** - Rear (not available on Geared Resolver) L - Left (120° from top on "A" housings)

S - Top Side